



1	2	40	41	42	43	44	45	46	47	48	49	50	88	89	90	91	92	93	94	95	96
1-1	1-2	1-40	-	-	-	-	-	-	-	-	1-80	1-79	1-41	CDM1	-	-	-	-	-	-	-
2-1	2-2	2-40	-	-	-	-	-	-	-	-	2-80	2-79	2-41	-	CDM2	-	-	-	-	-	-
3-1	3-2	3-40	-	-	-	-	-	-	-	-	3-80	3-79	3-41	-	-	CDM3	-	-	-	-	-
4-1	4-2	4-40	-	-	-	-	-	-	-	-	4-80	4-79	4-41	-	-	-	CDM4	-	-	-	-
5-1	5-2	5-40	-	-	-	-	-	-	-	-	5-80	5-79	5-41	-	-	-	-	CDM5	-	-	-
6-1	6-2	6-40	-	-	-	-	-	-	-	-	6-80	6-79	6-41	-	-	-	-	-	CDM6	-	-
7-1	7-2	7-40	-	-	-	-	-	-	-	-	7-80	7-79	7-41	-	-	-	-	-	-	CDM7	-
8-1	8-2	8-40	-	-	-	-	-	-	-	-	8-80	8-79	8-41	-	-	-	-	-	-	-	CDM8
9-1	9-2	9-40	-	-	-	-	-	-	-	-	9-80	9-79	9-41	-	-	-	-	-	-	-	-
10-1	10-2	10-40	-	-	-	-	-	-	-	-	10-80	10-79	10-41	-	-	-	-	-	-	-	-
11-1	11-2	11-40	-	-	-	-	-	-	-	-	11-80	11-79	11-41	-	-	-	-	-	-	-	-
12-1	12-2	12-40	-	-	-	-	-	-	-	-	12-80	12-79	12-41	-	-	-	-	-	-	-	-
13-1	13-2	13-40	-	-	-	-	-	-	-	-	13-80	13-79	13-41	-	-	-	-	-	-	-	-
14-1	14-2	14-40	-	-	-	-	-	-	-	-	14-80	14-79	14-41	-	-	-	-	-	-	-	-
15-1	15-2	15-40	-	-	-	-	-	-	-	-	15-80	15-79	15-41	-	-	-	-	-	-	-	-
16-1	16-2	16-40	CDM6	-	-	-	-	-	-	-	16-80	16-79	16-41	-	-	-	-	-	-	-	-

front polarizer  
front class  
rear class  
rear polarizer

**FUTURE S&T(SHEN ZHEN)CO.,LCD**  
 TEL: +86-755-29675886, FAX: +86-755-29675495

DESIGNED BY: **FZYJB**  
**Y00008T-11**

CHECKED BY:   
 VERSION: 1.0  
 NO. 1 OF 1  
 UNIT: MM  
 DATE: 2005-06-16

NOTES:

1. DISPLAY TYPE: STN(Y-G)
2. LCD OPERATING VOLTAGE: 4.4V
3. OPERATING TEMPERATURE: -20°C~70°C
4. STORAGE TEMPERATURE: -30°C~80°C
5. DRIVE MODE: 1/16D, 1/4B
6. VIEWING DIRECTION: 6:00
7. POLARIZER TYPE: TRANSPARENT, POSITIVE
8. CONNECTOR: ZEBRA
9. CUSTOMER NO: HS6613