



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
NAME	VSS	VDD	V0	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	LED+	LED-

NOTE:
 1.DISPLAY TYPE: STN/Blue Mode/Negative
 2.LCD POLARIZER TYPE: Transmissive
 3.VIEWING DIRECTION: 6:00 O'CLOCK
 4.LCD OPERATING VOLTAGE: Vlcd:4.5 V
 5.DRIVE METHOD: 1/8DUTY,1/4BIAS
 6.OPERATING TEMP: -20 ~ +70°C
 STORAGE TEMP: -35 ~ +85°C
 7.LCD CONNECTOR: ZEBRA
 8.DISPLAY DRIVER: ST7066U-0A-B
 9.LED: Using 2*White LED VF=5.0V,IF=30mA
 10.Unspecified tolerance is ±0.20mm
 11.Rohs Request

飞优特科技(深圳)有限公司
 FUTURE S&T(SHEN ZHEN)CO.,LTD
 TEL: +86-755-29675886, FAX: +86-755-29675495
 E-mail:futurelcd@21cn.com

UNIT: MM SIZE: A4
 SHEET: 1 OF 4

LCM NO.:	SB08103-BKBW	DWG NO.:	B08103-BKBW-CD	REV:	A0
DRAWN BY:		CHECKED BY:		APPROVED BY:	