



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
NAME	VSS	VDD	V0	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	LED+	LED-

NOTE:

- 1.DISPLAY TYPE: HTN/W-B Mode/Positive
- 2.LCD POLARIZER TYPE: Transflective
- 3.VIEWING DIRECTION: 6:00 O'CLOCK
- 4.LCD OPERATING VOLTAGE: Vlcd:4.5 V
- 5.DRIVE METHOD: 1/8DUTY,1/4BIAS
- 6.OPERATING TEMP: 0 ~ +50°C
- 7.LCD CONNECTOR: -20 ~ +70°C
- 8.DISPLAY DRIVER: ZEBRA
- 9.LED: ST7066U-0A-B
- 10.Unspecified tolerance is ±0.20mm
- 11.Rohs Request Using 22*Yellow-GreenLED VF=5.0V;IF=110mA

飞优特科技(深圳)有限公司
FUTURE S&T(SHEN ZHEN)CO.,LTD
 TEL: +86-755-29675886, FAX: +86-755-29675495
 E-mail: futurelcd@21cn.com

UNIT: MM SIZE: A4
 SHEET: 1 OF 4

LCM NO.: SB08103-HEAV DWG NO.: B08103-HEAV-CD REV: A0

DRAWN BY: CHECKED BY: APPROVED BY: