



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
NAME	VSS	VDD	V0	RS	RW	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	LED+	LED-

NOTE:
 1.DISPLAY TYPE: STN/Y-G Mode/Positive
 2.LCD POLARIZER TYPE: Reflective
 3.VIEWING DIRECTION: 6:00 O'CLOCK
 4.LCD OPERATING VOLTAGE: Vcd:4.5 V
 5.DRIVE METHOD: 1/8DUTY,1/4BIAS
 6.OPERATING TEMP: 0 ~ +50°C
 STORAGE TEMP: -20 ~ +70°C
 7.LCD CONNECTOR: ZEBRA
 8.DISPLAY DRIVER: ST7066U-0A-B
 9.LED: NO BACK LIGHT
 10.Unspecified tolerance is ±0.20mm
 11.Rohs Request

飞优特科技(深圳)有限公司
FUTURE S&T(SHEN ZHEN)CO.,LTD
 TEL: +86-755-29675886, FAX: +86-755-29675495
 E-mail: futurelcd@21cn.com

UNIT: MM SIZE: A4
 SHEET: 1 OF 4

LCM NO.: SB08103-YANN DWG NO.: B08103-YENN-CD REV: A0

DRAWN BY: CHECKED BY: APPROVED BY: